PRODUCT BULLETIN

ROBULL® LCM

LOST CIRCULATION MATERIAL







PRODUCT DESCRIPTION

NO BULL® LCM is a blend of thermally processed, lightweight, 100% organic lignin and cellulose plant fibers recycled from dairy cow manure that interweave and plug fractures and voids immediately. Compatible with water or oil-based drilling fluids, NO BULL® LCM is proven to be a superior sealant in down-hole applications as well as extremely cost effective...a little goes a long way!

*Not recommended for absorbing strong oxidizing agents, strong acids or caustics.

** 7-to-1 claim on weight to weight absorption of water. Fluids and absorbency rates vary by product & application. Rates listed should be treated as approximations

BENEFITS

- PROVEN TO STOP MUD LOSS IMMEDIATELY
- HIGHLY COST EFFECTIVE
- ◆ USDA CERTIFIED BIOBASED PRODUCT 100%
- FOR ALL TYPES OF DRILLING FLUIDS
- ◆ 7X OIL ABSORPTION
- 100% BIODEGRADABLE
- ♦ EXPANDS 1.5 TIMES ITS ORIGINAL DRY SIZE
- STABLE IN HIGH-TEMP APPLICATIONS
- EASILY MIXES WITH ALL KINDS OF MUDS
- CONSISTENT QUALITY FROM BAG TO BAG
- SILICA-FREE
- MADE IN THE USA

SUSTAINABLE

- NOT HARMFUL TO THE ENVIRONMENT
- PRODUCTION OF LCM DOES NOT DEPLETE NATURAL RESOURCES
- ◆ 100% RECYCLED FROM VIRTUALLY UNLIM-ITED SOURCES

APPLICATION

Typically mixed at 2 lbs per barrel of mud, NO BULL® LCM is highly cost effective compared to other LCM products, organic or synthetic.

Manufactured by NO-BULL® A Division of NCS, Inc. 130 Industrial Dr. Chambersburg, PA 17201 717-261-5711 www.nobullsupply.com



SPECIFICATION & PACKAGING

IN BULL LCM LOST CIRCULATION MATERIAL







HANDLING AND STORAGE

Store in cool, dry well-ventilated area away from ignition sources and strong oxidizing agents. Please review the Safety Data Sheet thoroughly before using this product under resources at www.nobullsupply.com.

TYPICAL PHYSICAL PROPERTIES

Appearance Brown, fibrous material
Specific Gravity 0.16
Water Solubility minimal
Bulk Density
Acid Solubility 65% soluble in 15% Hydrochloric acid
Moisture10%

PARTICLE SIZE DISTRIBUTION

Retained on 10 Mesh	19.6%
Retained on 20 Mesh	20.6%
Retained on 40 Mesh	24.9%
Retained on 60 Mesh	17.8%
Retained on 80 Mesh	5.9%
Passing 80 Mesh	9.1%

PACKAGING

No-Bull® LCM is available in UV resistant 10 lb bags with a waterproof UV resistant hood via full truck loads or by the pallet.

Shrink-wrapped pallet: 66 bags Full truckload: 1,716 bags

Manufactured by NO-BULL® A Division of NCS, Inc. 130 Industrial Dr. Chambersburg, PA 17201 717-261-5711 www.nobullsupply.com



Sustainable Solutions